HIT HOFMAN S. R. O.

Road safety first

Large halogen lamp set VHS20-10

The large lamp set is a signalling device for guiding traffic in crosswise as well as lengthwise closures of up to 100m on roads.

If more than 10 lamps need to be synchronised, by connecting two control units we get a set of 20 lamps. For connecting the control units, a connector needs to be added to both control units as well as a connecting cable.

CONTROL UNIT VHR10-230V/12V HALOGEN

- up to 10 independent halogen lamps HS20-xx can be connected to the control unit
- the control unit includes six functional modes:
 - 1. one light moves from 1 to 10
 - 2. two lights move simultaneously from 1 to 10
 - 3. lights from 1 to 10 are switched on one after another and then switched off in the same sequence
 - 4. lights from 1 to 10 are switched on one after another and then switched off all at the same time
 - 5. lights from 1 to 10 are switched on one after another, switched off all at the same time and then they flash all at once
 - 6. Odd lights are flashing against even ones
- includes the 24-hour as well as only-at-night option
- at night, electronics automatically reduce luminous intensity, to provide better orientation the lamps also have a backlight
- moreover, the electronics include reverse polarity protection and protect the battery from deep discharge
- in case of the 230V power failure, the control unit automatically switches to the 12 V battery
- in case of a 230V supply while the battery is connected, the capacity of the (connected) battery is maintained via a recharging circuit on the controlling electronics (no self-discharge of the battery)

Control unit VHR10-12V halogen has identical functions but it can only be supplied from a 12V battery.

PROTECTION OF THE LAMP CONTROL UNIT AND THE BATTERY

the lamp control unit together with the battery of up to 12V/230Ah is placed in a standard lockable metal-sheet box or a robust safety











THE SET OF 10 LAMPS IN MODE 1 SUPPLIED FROM BATTERY 12V/18OAH KEEPS FLASHING NONSTOP FOR UP TO 140 HOURS, IN MODE 3 FOR UP TO 31 HOURS

www.hit-hofman.cz



Road safety first

battery box

the battery box protects the battery and the lamp control unit against weather conditions and theft

HALOGEN LAMP HS20-XX

- halogen lamp ø200mm EN 12352 L8H
- the lamps is connected by a 10, 20, 30, 40, 50m cable with connector
- the lamps can be attached to a profile of ø43mm or 40x40mm

Technical data for consumption in the chart refer to a set of 10 lamps and selected modes.

TECHNICAL DATA

Power supply	12V= / 230V/50Hz
Current consumption 12V=	1. day 1,6A night 1,0A
Average consumption 12V=	1. 31Ah / 24 hours
Current consumption 12V=	2. day 3,2A night 2,0A
Average consumption 12V=	2. 62Ah / 24 hours
Current consumption 12V=	3. day 7,3A night 4,3A
Average consumption 12V=	3. 140Ah / 24 hours
Current consumption 12V=	4. day 6,5A night 3,8A
Average consumption 12V=	4. 123Ah / 24 hours
Current consumption 12V=	5. day 4,8A night 2,9A
Average consumption 12V=	5. 92Ah / 24 hours
Current consumption 12V=	6. day 7,0A night 4,1A
Average consumption 12V=	6. 133Ah / 24 hours
Protection degree	IP44



Road safety first

PRODUCTS

Order no.	Product name	Quantity
1-080-000121	Halogen lamp HS20-10	1 pc.
1-080-000122	Halogen lamp HS20-20	1 pc.
1-080-000123	Halogen lamp HS20-30	1 pc.
1-080-000124	Halogen lamp HS20-40	1 pc.
1-080-000125	Halogen lamp HS20-50	1 pc.
1-080-000210	Battery box with halogen controller VHR10- 230V/12V	1 pc.
1-080-000220	Robust battery box with halogen controller VHR10- 230V/12V	1 pc.
1-080-000250	Battery box with halogen controller VHR10-12V	1 pc.
1-080-000260	Robust battery box with halogen controller VHR10- 12V	1 pc.
1-099-000050	Additional VR connector for connecting controllers	1 pc.
1-099-000100	Patch cord PK-R-100	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
2-890-010020	Battery 12V/180Ah	1 pc.
2-045-015010	Delineator panel HIT-2.L arrow 60/60	1 pc.
2-045-015020	Delineator panel HIT-2.LP arrow 60/60	1 pc.
2-045-015040	Delineator panel HIT-2.PP arrow 60/60	1 pc.
2-045-090010	Adapter Z4/lamp 60/40	1 pc.
2-050-000000	Base plate HIT	1 pc.