


Light arrow SS15 LED with motor-operated lifting SD SS-2

Motor-operated frame is for lifting or lowering of the light arrow using a linear actuator controlled by remote control from the driver's cabin. Light arrow is a signalling device used for maintenance vehicles, gritters, road sweepers, marking vehicles and trailers, or it can be used for indicating road works and the direction of its drive-around. This light arrow is also described as **Light arrow and cross type B**, warning arrow or signalling arrow.

- > **15 LED lamps** ø200mm **EN 12352 L8H**
- > main advantage of the light arrow with 15 lamps is a more visible symbol of cross
- > electronics automatically reduce lamp luminous intensity at night and includes reverse polarity protection
- > moreover, the electronics protect the battery from deep discharge by disconnecting the light arrow symbols depending on the current battery status
- > **remote control with 15m cable** for control and optical check of the function modes and displaying the position of the light arrow
- > the light arrow has the following modes: arrow to the left, arrow to the right and cross
- > all operational information are clearly displayed on the remote control
- > **10m power supply cable** to be installed on the vehicle
- > the collapsible frame with light arrow can be attached to a profile of up to (WxH) 40x30mm (roof racks)
- > the light arrow is lifted / lowered using by a robust linear actuator controlled by remote control from the driver's cabin
- > the actuator has a bolt enabling manual lifting or lowering of the light arrow in case of failure or emergency
- > electronics protect the actuator and the frame construction against overloading using a current-limit protection
- > **power supply voltage 12/24V=**, average current consumption of actuator 12V=8,5A



LIGHT ARROW SS15 LED SUPPLIED FROM BATTERY 12V/180AH KEEPS FLASHING NONSTOP FOR UP TO 11 DAYS

TECHNICAL DATA

| | |
|--------------------------|--------------------------|
| Power supply | 12/24V= |
| Current consumption 12V= | day 1,0A night 0,4A |
| Average consumption 12V= | 16,4Ah / 24 hours |
| Current consumption 24V= | day 0,55A night 0,23A |
| Average consumption 24V= | 9,2Ah / 24 hours |
| Flashing frequency | 60/min. |
| Dimensions (WxHxL) | 980x380x1130mm |
| Weight | 50kg |

PRODUCTS

| Order no. | Product name | Quantity |
|--------------|---|----------|
| 1-140-355020 | Light arrow SS15 LED with motor-operated lifting SD SS-2 | 1 pc. |

ACCESSORIES

| Order no. | Product name | Quantity |
|----------------|---|----------|
| 1-035-020200 | Wireless remote control SS15-2 02 MZS RADIO | 1 pc. |
| 3-580-10000100 | Remote control bracket DO-082 | 1 pc. |