

## Machinery transport trailer TPM-35.2S\_01


Machinery transport trailer with warning board for indicating road works and for transporting small vibratory rollers, excavators and other road work machinery. This warning trailer with flashing arrow is also described as Traffic device Z7 – **Mobile road closure sign type II**.

- > strong two-axle trailer with overrun device and hand brake, hot-dip galvanized
  - > height adjustable overrun device with replaceable coupling device for ball ø50mm or as accessories pin DIN ø40mm or ø50mm
  - > full-size spare wheel
  - > loading ramp lifted with the support of gas springs
  - > two side supports for stability and safety while loading machinery
  - > **trailer LED lighting with a 13-pin plug that can be connected to the towing vehicle with 12V as well as 24V onboard voltage**
  - > loading area of water-resistant anti-slip plywood with 400mm solid side walls
  - > four lashing rings to tie the loaded machinery
  - > loading ramp and flooring are covered by anti-slip cast rubber
  - > battery box (WxHxL) 600x300x330mm for battery of up to 12V/230Ah
- 
- > two-part retroreflective warning board (WxH) **1700x2500mm**, red and white stripes **300mm** wide (class RA2) with the blue round traffic sign **ø900mm** (class RA2), and a manually rotatable white arrow
  - > the upper board can be lifted by a lifting rod supported by gas springs while secured against wind pressure in the operating position
  - > the warning board has two positions: frontal transport position **leaving enough space for the loaded machinery** and rear operating position where it forms a compact retroreflective warning board, the board can be moved easily between both positions



### TRAILER VARIANTS

- > traffic signs can be modified according to national standards
- > total weight of the **braked trailer can be between 2500kg and 3500kg**



## TECHNICAL DATA

Total weight	3500kg
Trailer weight	1168kg
Payload	2332kg
Overall length	5760mm
Overall width	1990mm
Transport height	2460mm
Operational height	3460mm
Loading area (WxL)	1495x3220mm

TRAILER IS ALSO AVAILABLE  
WITHOUT THE WARNING BOARD  
ONLY FOR THE TRANSPORT OF  
MACHINERY

## PRODUCTS

Order no.	Product name	Quantity
1-050-002100	<b>Machinery transport trailer TPM-35.2S_01</b>	1 pc.
1-040-008010		1 pc.

## ACCESSORIES

Order no.	Product name	Quantity
1-035-005025	<a href="#">NZSP-1 01 Light arrow SS13-L LED</a>	1 pc.
1-035-005520	<a href="#">NZSP-1 01 Extension of light arrow to SS15 LED</a>	1 pc.
2-890-010020	<a href="#">Battery 12V/180Ah</a>	1 pc.
2-895-092170	<a href="#">ZSP 01 Battery charger 12V/17A</a>	1 pc.
2-895-101120	<a href="#">Adapter 7 to 13 pins 12V</a>	1 pc.
4-300-13003100	<a href="#">Eye end D40 3500kg</a>	1 pc.
4-300-13003200	<a href="#">Eye end D50 3500kg</a>	1 pc.