HIT HOFMAN S.R.O.

Road safety first

Warning trailer ZSP-10.1Z_01

Warning trailer for indicating road works on highways and dual carriageways and for transporting traffic signs, base plates or tools. This trailer with flashing arrow is also described as **Traffic device Z7 – Mobile road closure sign type I.**

The lower board of this **ZSP-10.1Z** version is hinged and can be lifted.

- strong one-axle trailer with overrun device and hand brake, hot-dip galvanized
- height adjustable overrun device with replaceable coupling device for ball ø50mm or as accessories pin DIN ø40mm or ø50mm
- full-size spare wheel
- two side supports for stability while standing
- trailer LED lighting with a 13-pin plug that can be connected to the towing vehicle with 12V as well as 24V onboard voltage
- Ioading area of water-resistant anti-slip plywood with 350mm solid side walls
- Iockable battery box with aluminium sheet lid (WxHxL) 1660x350x400mm for one or two batteries with a capacity of up to 12V/230Ah
- two-part retroreflective warning board (WxH) 2200x3600mm, red and white stripes 500mm wide (class RA2) with the blue round traffic sign ø1500mm (class RA2), which includes view-through slots to monitor the rear traffic for workers' enhanced safety, and a motor-driven rotatable arrow
- the upper board can be lifted by a lifting rod supported by gas springs while secured against wind pressure in the operating position
- the lower board can be lifted with the support of gas springs, clearance width 1620mm, clearance height 1760mm

TRAILER VARIANTS

- traffic signs can be modified according to national standards
- power supply from fuel cell battery charger
- total weight of the braked trailer can be between 900kg and 1600kg













THE HINGED LOWER BOARD MAKES LOADING OF THE TRAILER VERY EASY

www.hit-hofman.cz

HIT HOFMAN, s.r.o. Pražská 333 CZ-252 44 Psáry Copyright © 2024 HIT HOFMAN, s.r.o. Tel: +420 241029960

E-mail: hit@hit-hofman.cz 29.4.2024 1/2

HIT HOFMAN S.R.O.

Road safety first

TECHNICAL DATA

Total weight	1300kg
Trailer weight	664kg
Payload	636kg
Overall lenght	4060mm
Overall width	2200mm
Transport height	2660mm
Operational height	3970mm
Loading area (WxL)	1670x1985mm

PRODUCTS

Order no.	Product name	Quantity
1-010-000300	Warning trailer ZSP-10.1Z_01	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-015-005025	NZSP-10_01 Light arrow SS25-L LED	1 pc.
1-015-010000	Wireless remote control SS25-1_02 RADIO	1 pc.
1-015-200010	NZSP-10_01 Board lift drive MZS 12V	1 pc.
2-890-010020	Battery 12V/180Ah	1 pc.
2-895-092250	ZSP_01 Battery charger 12V/25A	1 pc.
1-015-270910	ZSP-10_01 Set for second battery	1 pc.
2-895-092300	ZSP_01 Battery charger 12V/30A	1 pc.
2-895-101120	Adapter 7 to 13 pins 12V	1 pc.
3-580-10000200	Remote control bracket TAS-100	1 pc.
1-015-280020	Drive-up ramp NR-ZSP-10	1 pc.
1-015-281010	Winch with bracket for ZSP-10	1 pc.
4-300-13002100	Eye end D40 3000kg	1 pc.
4-300-13002200	Eye end D50 3000kg	1 pc.

www.hit-hofman.cz

E-mail: hit@hit-hofman.cz 29.4.2024 2 / 2