HIT HOFMAN S.R.O.

Road safety first

Light arrow SS15 LED with motor-operated lifting SD SS-2

Motor-operated frame is for lifting or lowering of the light arrow using a linear actuator controlled by remote control from the driver's cabin. Light arrow is a signalling device used for maintenance vehicles, gritters, road sweepers, marking vehicles and trailers, or it can be used for indicating road works and the direction of its drive-around. This light arrow is also described as **Light arrow and cross type B**, warning arrow or signalling arrow

- 15 LED lamps ø200mm EN 12352 L8H
- main advantage of the light arrow with 15 lamps is a more visible symbol of cross
- electronics automatically reduce lamp luminous intensity at night and includes reverse polarity protection
- moreover, the electronics protect the battery from deep discharge by disconnecting the light arrow symbols depending on the current battery status
- remote control with 15m cable for control and optical check of the function modes and displaying the position of the light arrow
- the light arrow has the following modes: arrow to the left, arrow to the right and cross
- all operational information are clearly displayed on the remote control
- 10m power supply cable to be installed on the vehicle
- the collapsible frame with light arrow can be attached to a profile of up to (WxH) 40x30mm (roof racks)
- the light arrow is lifted / lowered using by a robust linear actuator controlled by remote control from the driver's cabin
- the actuator has a bolt enabling manual lifting or lowering of the light arrow in case of failure or emergency
- electronics protect the actuator and the frame construction against overloading using a current-limit protection
- power supply voltage 12/24V=, average current consumption of actuator 12V=8.5A











LIGHT ARROW SS15 LED SUPPLIED FROM BATTERY 12V/18OAH KEEPS FLASHING NONSTOP FOR UP TO 11 DAYS



Road safety first

TECHNICAL DATA

Power supply	12/24V=	
Current consumption 12V=	day 1,0A night 0,4A	
Average consumption 12V=	16,4Ah / 24 hours	
Current consumption 24V=	day 0,55A night 0,23A	
Average consumption 24V=	9,2Ah / 24 hours	
Flashing frequency	60/min.	
Dimensions (WxHxL)	986x378x1129mm 48,2kg	
Weight		

PRODUCTS

Order no.	Product name	Quantity
1-140-355020	Light arrow SS15 LED with motor-operated lifting SD SS-2	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-035-020200	Wireless remote control SS15-2 02 MZS RADIO	1 pc.
3-580-10000100	Remote control bracket DO-082	1 pc.