



## Lightbar SR-5 with beacon adapters

Lightbar is a signalling device used for maintenance vehicles, gritters, road sweepers, marking vehicles, police and fire-brigade vehicles. **This lightbar includes two adapters** to attach **flexible or firm-base beacons** to improve the warning effect

- > **5 halogen lamps ø200mm EN 12352 L8H**
- > electronics automatically reduce lamp luminous intensity at night and includes reverse polarity protection
- > moreover, the electronics protect the battery from deep discharge by disconnecting the light arrow symbols depending on the current battery status
- > **remote control with 10m cable** for control and optical check of the function modes
- > all operational information are clearly displayed on the remote control
- > **10m power supply cable** to be installed on the vehicle
- > using clamps, the lightbar can be attached to a profile of up to (WxH) 40x30mm (roof racks)
- > **basic width of the lightbar is 1406mm**, other available widths 1550, 1800, 2050 and 2310mm
- > includes **two adapters** to attach **flexible or firm-base beacons**
- > beacons are switched on separately using a switch with an indicator light
- > beacons are not included in the delivery, suitable beacons can be found in the list of accessories below
- > the lightbar has 6 modes
  - Mode 1. Light moves to the left
  - Mode 2. Light moves to the right
  - Mode 3. Two side lights are flashing
  - Mode 4. Even lights are flashing against odd ones
  - Mode 5. Lights move from the centre to the sides
  - Mode 6. All lights are flashing simultaneously



THE PRODUCT SECTION OFFERS  
ALSO A LIGHTBAR WITH A LOWER  
NUMBER OF LAMPS SR-4

**Technical data for consumption in the chart do not refer to the beacons for modes 4. and 6., for modes 1. and 2. the consumption is even 60% lower.**

## TECHNICAL DATA

Power supply	12/24V=
Current consumption 12V=	day 3,6A    night 2,25A
Average consumption 12V=	70Ah / 24 hours
Current consumption 24V=	day 2,0A    night 1,26A
Average consumption 24V=	39,4Ah / 24 hours
Flashing frequency	55/min.
Dimensions (WxHxL)	1406x230x140mm
Weight	8,1kg

## PRODUCTS

Order no.	Product name	Quantity
1-160-200025	<b>Lightbar SR-5 with beacon adapters</b>	1 pc.
1-160-200024	<b>Lightbar SR-4 with beacon adapters</b>	1 pc.
1-150-990100	<b>SR - Additional charge over basic dimension 250mm</b>	1 pc.
1-150-990200	<b>SR - Additional charge over basic DO in 5m</b>	1 pc.

## ACCESSORIES

Order no.	Product name	Quantity
2-010-101080	<a href="#"><u>Beacon LED-CR8 - T/L12-24/O pole mount</u></a>	1 pc.
2-010-102160	<a href="#"><u>Beacon LED-BPL - P/L12-24/O flexi mount</u></a>	1 pc.
2-010-102060	<a href="#"><u>Beacon LED-PAL - P/L12-24/O flexi</u></a>	1 pc.
2-010-010210	<a href="#"><u>Mini beacon M - P/H12/O flexi mount</u></a>	1 pc.
2-010-010220	<a href="#"><u>Mini beacon M - P/H24/O flexi mount</u></a>	1 pc.
3-580-10000100	<a href="#"><u>Remote control bracket DO-082</u></a>	1 pc.