

Signalling halogen lamps with bracket 12V=

Signalling lamps for enhanced road safety. Especially attached to highlight traffic signs, lane closure markers and roadblocks (barriers).

- > **SHS20-x.K halogen lamps** ø200mm **EN 12352 L8H**
- > **SHS10-x.K halogen lamps** ø200mm **EN 12352 L8M**
- > lamps flashing in **synchronous mode**
- > electronics automatically reduce luminous intensity at night
- > moreover, the electronics include reverse polarity protection and protect the battery from deep discharge
- > **5m power supply cable with battery terminals**, 3m length between each lamp
- > the lamps can be attached to a **profile of ø43mm or 40x40mm**



Technical data in the chart refer to one L8H signalling lamp.

TECHNICAL DATA

Power supply	12V=
Current consumption 12V=	day 0,64A night 0,40A
Average consumption 12V=	12,2Ah / 24 hours
Flashing frequency	44/min.
Dimensions (WxHxL)	200x245x145mm
Weight	0,95kg



SET OF THREE L8H HALOGEN LAMPS
SUPPLIED FROM BATTERY 12V/180AH
KEEPS FLASHING NONSTOP FOR UP
TO 5 DAYS

PRODUCTS

Order no.	Product name	Quantity
1-210-200011	Signalling halogen lamp SHS10-1.K	1 pc.
1-210-200012	Twin signaling halogen lamp SHS10-2.K	1 pc.
1-210-200013	Triple signalling halogen lamp SHS10-3.K	1 pc.
1-210-200021	Signalling halogen lamp SHS20-1.K	1 pc.
1-210-200022	Twin signalling halogen lamp SHS20-2.K	1 pc.
1-210-200023	Triple signalling halogen lamp SHS20-3.K	1 pc.

ACCESSORIES

Order no.	Product name	Quantity
1-220-900100	<u>Switch for lamps SS-x</u>	1 pc.
2-890-010020	<u>Battery 12V/180Ah</u>	1 pc.
1-110-100100	<u>Small lockable battery box UZA-M/M</u>	1 pc.
1-180-010010	<u>Collapsible barrier LZ-Z2-1</u>	1 pc.
1-180-010030	<u>Collapsible barrier LZ-Z2-2-SS</u>	1 pc.